

Take a load off. Relax.

PG 8080 ProfiLine Dishwasher



Take a load off. Relax.

PG 8080 ProfiLine Dishwasher

Overview

The Miele PG 8080 dishwasher offers the perfect solution for dealing with workplace crockery quickly and thoroughly.

Features & Benefits

- Easy to use controls
- 9 programme options
- 24h start delay
- Up to 75° main wash, 85° rinse option on hygiene programme
- PG 8080 U available as built-under model with adjustable plinth depth
- Child proof lock
- Connection for liquid detergent (external pump required)
- Can be connected to auto liquid dispenser (optional)
- Capacity for 13 place settings
- Shortest cycle time – 18 minutes (32AMP version connected to hot water)

Miele commercial dishwashers are built to the high standards Miele is renowned for and tested for 15,000 hours use. No other brand can claim such a strong commitment to quality, durability and reliability.

By installing a Miele commercial dishwasher in your business you are ensuring that your business is compliant to EU machinery guideline 2006/42/EG.



COMPLIANT
WITH MACHINERY
GUIDELINE
2006/42/EG



Technical Details: Overview

Dishwasher	PG 8080
Dimensions H/W/D (mm):	845/598/600
Weight (kg):	69
Electricity supply	230 V 50Hz
Total connected load:	(13AMP) 2.1kW/6.5kW (32AMP)
Water connections:	Single inlet hose for cold or hot water 1-10 bar pressure. Drain pump DN22; delivery head: 100 cm; max drainage length: 400cm



Decided? Get in touch

Miele Professional Limited
Fairacres
Marcham Road
Abingdon
Oxon
OX14 1TW

T: 0845 330 3618

E: miele-professional@miele.co.uk

W: www.miele-professional.co.uk

Take a load off. Relax.

PG 8080 ProfiLine Dishwasher

Consumption Data

Model: PG 8080 & PG 8080 U
Load: 13 place settings
Heater rating: 6.5 kW

Programme	Parameter Main wash °C/ °C	Water intake	Cold water connection (15°C)				Hot water connection (55°C)			
			Energy kWh	Cycle time	Optional Extra drying (min)	Total cycle time	Energy kWh	Cycle time	Optional Extra drying (min)	Total cycle time
Short	65/65	17	1.6	24	15	39	0.9	18	15	33
Medium	65/65	17	1.7	37	30	67	1	31	30	61
Intensive	75/65	23	1.9	53	30	83	1	46	30	76
Glasses	50/50	17	1	23	20	43	0.4	18	20	38
Hygiene	75/82	23	2.1	-	-	88	1.2	-	-	81
Eco	41.5/49.5	17	tba	-	-	118	0.4	-	-	112
Plastics	50/60	23	1.3	-	-	84	0.5	-	-	77
Beer glasses	50/-	17	0.6	19	-	19	0.4	17	-	17
Pre-wash/rinse	Cold water	5	0.03	11	-	11	0.03	11	-	11

Model: PG 8080 & PG 8080 U
Load: 13 place settings
Heater rating: 2.1 kW

Programme	Parameter Main wash °C/ °C	Water intake	Cold water connection (15°C)				Hot water connection (55°C)			
			Energy kWh	Cycle time	Optional Extra drying (min)	Total cycle time	Energy kWh	Cycle time	Optional Extra drying (min)	Total cycle time
Short	65/65	17	1.7	56	15	71	1	36	15	51
Medium	65/65	17	1.8	70	30	100	1	49	30	78
Intensive	75/65	23	2	85	30	115	1.1	61	30	91
Glasses	50/50	17	1.1	42	20	62	0.4	26	20	46
Hygiene	75/82	23	2.3	90	-	121	1.3	-	-	97
Eco	41.5/49.5	17	tba	-	-	135	0.4	-	-	119
Plastics	50/60	23	1.4	-	-	109	0.5	-	-	86
Beer glasses	50/-	17	0.7	31	-	31	0.4	24	-	24
Pre-wash/rinse	Cold water	5	0.03	11	-	11	0.03	11	-	11